

IMMER FILTER SHEETS

Filtration process is a separation technique aiming to obtain chemical, physical and microbiological stability of the filtrate. This goal, in the beverage industry, must be achieved respecting the organoleptic characteristics of the product to be filtered. The knowledge and the correct use of the depth filtration process allow enhancing the product's characteristics by taking away those rough sensations that could cover the more delicate ones.

Beverage filtration is therefore not just a simple separation mechanism; in wine (as well as in vinegar, fruit juice etc.) aroma, tonality and intensity of the color are components that, if "ill-treated", would result in a poor product and so in a lower price range. Filtering without stressing and impoverishing the original product is possible today with the new line of **IMMER** Filter-sheets. They are the result of an attentive project where:

- Sieving and Adsorption mechanisms do act aiming specifically to the unstable fraction of the product.
- The filtering medium is manufactured with a calibrated and asymmetric structure with a high empty/full ratio which is equal or over 80% of the available volume.
- Cellulose particles do incorporate the other filtering aids in one single and stable body.
- Filtration of food beverages do require selected raw materials; for this reason, their chemical and physical characteristics are tested before, during the process and finally on the finished product in order to guarantee the final user with maximum safety and best performances.
- The available range of products allows for an accurate choice of type and size of the filter-sheet best fitted for a given technological goal.
- The traceability of the product is guaranteed by strict Quality Control procedures.

TECHNICAL CHARACTERISTICS

IMMER filter-sheets are the result of a balanced relation between selected raw materials that are carefully processed, aiming to offer the following advantages:

"Fraction Filtration" with retention of the unstable fraction, mainly in the depth of the sheet's body, thanks to its asymmetric structure and to its high empty/full ratio; in this way, we avoid the inconvenient that may be caused by the accumulation of the dirt on the surface, accumulation that would result in a reduction of the specific permeability of the filter-sheet, modifying also its retention capability and causing its early blocking.









IMMER FILTER SHEETS

- Respect of color and other compound in solution thanks to the balanced Zeta Potential which acts mainly on unstable fractions improving, besides the product's stability, also its filterability in consideration of possible further filtrations such as membrane filtration.
- Superior mechanical resistance for a consistent quality of filtration even at increasing or varying pressure; with this, dripping problems are also reduced as well as the transfer of undesired substances into the filtrate. Furthermore, this characteristic will make the removal of the exhausted sheets easier, avoiding rupture and pulping of the sheet itself.
- Definite and safe micro-biological retention of yeast, bacteria and mold for sterilizing sheets thanks to the high LRV (Logarithmic Reduction Value).
- Practically irrelevant ion transfer thanks to the purity of the raw materials employed.
- A complete range of filter-sheets for beverage filtration (coarse, polishing and sterile filtration), available in several different sizes.
- Consistent quality.

Strato IMMER		IMS1	S <mark>M</mark> IS	=	MS50	MS30	MS20	M10	M7	M5	M3	M2	M1
Filtrazione		=	Ste		Σ		≥ rillar				gros		
00000000	0,1										1000000		
85::885	0,2					11188111				(8:1: (8)	: 333: : : : 3		X8::3X:
900 11 900 C	0,3	110011100			1000011110	1110000111	69 : ::69::	1109 1110	:::::00	90000000	18001110	R:::X0::::	08:1800
0015300010	0,4	9199911	dervoe			***********	(K)(K) (S)(K)(K)	1 (000 1 (d) 1 (d) (d) (d)	3186013	011000	000001000 00001000	1000100	RC1959C1
8811881	0,6	15/8 11/8	58	502111501	1992		01:1500:	199 (19)	80	5011150	10001110	111000	000110001
	0,8			000000	: 5(5)(52:115)	111000111		130 1139		9811198		111080111	8000
porosità (µm)	1,0	138118		98511387	13851131	11109	@ :: <u>305</u>			38:::38	188113	11130000	8811381
	1,5		11100	8388		1.000	0 ::00	1000 1100		60-1-60		111,021	00000
) iso	2,0	:::83:::38	:::3:8 :::	865::386	188651180			:::811:::8					
Ö	2,5	11/80011408		864 (188)	1 200004 11200	111566111	(6) 110(6)	11/8/10/11/80	5111136911				
80:1000	3,0	11881188	H11908 111	\$00000	150021150	11188111	98 1138 R	11801118	011199011				
80.000	4,0			60	- 000		101	991-99	9.5				
66 m 66 m	5,0	11000		60: ::::601	150000000	: ::::::::::::::::::::::::::::::::::::							000000








IMMER FILTER SHEETS

A general characteristic of the filtering media is the relation between the yield and the retention grade, where one is in inverse proportion to the other. As an example, the table to the right reports a diagram showing such relation.

IMMER Filter-Sheets do perform with high yields and a consistent quality of filtration.

Permeability of filter sheets is higher in coarser types and lower in sterile ones. This difference, considering the range of **IMMER** filter sheets, is higher than 1: 30 when we compare IMS1 to M1; **IMMER**'s range is able to satisfy the most different applications.

For wine filtration we recommend the flux shown in the diagram, based on the different applications.



Strato IMMER	LRV
IMS1	>9
IMS	>8,3
IM	>6,8
MS50	>6,1

IMMER Filter Sheets of sterile type are characterized by a high LRV (Logarithmic Reduction Value) in reference to yeast and bacteria.

The table shown to the left refers to lactic bacteria. This characteristic allows for their use also as a final filter.



Via Pacinotti, 37 – 30020 Pramaggiore (VE)

T: +39 0421 200 455 | F: +39 0421200460